



HD VISIBLE AND THERMAL PAN/TILT

FLIR Triton™ PT-Series HD

The FLIR Triton™ PT-Series HD is our most advanced dual-sensor security system, combining a cooled or uncooled thermal sensor with 640 × 480 resolution, a 1080p HD visible-light imaging sensor, and a high speed, precision pan/tilt system. The Triton PT-Series HD integrates easily with FLIR United VMS 8.0, as well as other major third party video management systems, making it an extremely versatile solution for critical infrastructure protection in total darkness, bright sun, and adverse conditions.

www.flir.com/pt-series



SUPERIOR IMAGE QUALITY

PT-Series HD provides unmatched perimeter protection, regardless of lighting conditions.

- 640x480 resolution thermal camera sees clearly in complete darkness or bright sunlight, through smoke, dust and light fog
- High-performance thermal lens with 4X optical zoom and auto-focus
- 1080p HD camera with 30X optical zoom and outstanding low light performance



RUGGED HOUSING

A weather-resistant design withstands harsh environments, reducing maintenance time.

- Deicing and de-fogging capabilities
- Sun-safe VOx uncooled thermal sensor technology
- Rated IP66 for dust and water ingress
- Vandal-resistant



DESIGNED FOR SYSTEM INTEGRATION

Enhanced capabilities are enabled when controlled using FLIR United VMS

- Integrates with FLIR's United VMS for such options as a fully-programmable preset tour, dual-sensor viewing mode, and alarm functions.
- Open IP standards for plug-and-play integration with 3rd party VMSs and devices
- Simultaneous IP and analog outputs of thermal and visible-light video
- ONVIF compliant

SPECIFICATIONS

Thermal Camera Specs			
Array Format (NTSC)	640 x 480		
Detector Type	Long-Life, Uncooled VOx Microbolometer		
Effective Resolution	307,200		
Pixel Pitch	17 µm		
Thermal Frame Rate	NTSC: 30 Hz PAL: 25 Hz / 8.3 Hz		
Optical Characteristics	Model	FOV	Focal Length, F#
	PT-644 HD	44°x36°	13 mm, f/1.0
	PT-625 HD	25°x18°	25 mm, f/1.1
	PT-617 HD	17°x14°	35 mm, f/1.1
	PT-612 HD	12°x10°	50 mm, f/1.2
	PT-608 HD PT-606Z HD	8.6°x6.6° Uncooled continuous zoom 24° to 6°	75 mm, f/1.1 26-105 mm, f/1.6
E-Zoom	Continuous E-Zoom to 4x		
Spectral Range	7.5 µm to 13.5 µm		
Focus Range	Athermalized, Focus-Free		
Sensitivity	<35mK @ 25c F# 1.0		
Video			
Composite Video NTSC or PAL	Yes: Hybrid IP & Analog		
Video Compression	Two independent channels of H.264 & M-JPEG for each sensor		
Streaming Resolution	Thermal: QVGA to VGA Visible: VGA to HD		
Thermal Image Settings	Auto AGC, Dynamic Detail Enhancement (DDE), Sensitivity		
Thermal AGC Region of Interest (ROI)	Default, Presets and User definable to insure optimal image quality on subjects of interest		
Image Uniformity Optimization	Automatic Flat Field Correction (FFC) - Thermal and Temporal Triggers		
System Integration			
Ethernet	Yes		
Serial Control Interfaces	RS-232/-422; Pelco D, Bosch		
External Analytics Compatible	Yes		
Network APIs	FLIR SDK FLIR CGI ONVIF Profile S		
Network			
Supported Protocols	IPv4, HTTP, Bonjour, UPnP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, IGMP, DHCP, ARP, HTTPS		
Pan/Tilt Performance			
Pan Angle / Speed	Continuous 360°; 0.1° to 60°/sec		
Tilt Angle / Speed	+90° to -90°; 0.1° to 30°/sec		
Programmable Presets	256		

Specifications are subject to change without notice.
For the most up-to-date specs, go to www.flir.com

General	
Operating Temperature Range	-40°C to 70°C
Weight	~37 lb (16.8 kg); Configuration Dependent
Dimensions (L, W, H)	13.7, 18.4, 12.8" (348, 467, 326 mm)
Input Voltage	24 VDC (21-30 VDC) 24 VAC (21-30 VAC)
Power Consumption	24 VAC: 85 VA (max w/o heaters) 215 VA (max w/heaters) 24 VDC: 65 W (max w/o heaters) 195 W (max w/heaters)

Environmental	
IP Rating (Dust & Water Ingress)	IP66
Operating Temperature Range	-40°C to 70°C cold start
Storage Temperature Range	-55°C to 85°C
Humidity	0-95% relative
Shock	MIL-STD-810F "Transportation"
Vibe	IEC 60068-2-27
De-Icing / Anti-Icing	MIL-STD-810F, Method 521.1; – De-Icing of 3/6mm pending model

Compliance & Certifications	
FCC Part 15 (Subpart B, class A)	
CE Marked	
RoHS	
IP66	
ONVIF Profile S	
WEEE	

Visible Light Camera	
Sensor Type	Full HD 1080p 1/2.8-type Exmor R CMOS
Sensor illumination	Back Light Compensation
Low light sensitivity	Color: 0.01 lx (F1.6, AGC on, 1/30s)
Noise reduction	Yes (6 steps)
WDR	120dB
F/#	F1.6 to F4.7
Lens Field of View	63.7° (wide end) to 2.3° (tele end)
Focal Length	4.3 mm (wide) to 129.0 mm (tele)
Zoom	30X optical zoom with auto-focus and 12X digital zoom

Cyber Security	
IEEE 802.1x	
TLS/HTTPS	
User authentication	
Access control via firewall	

CORPORATE HEADQUARTERS
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 877.773.3547

SANTA BARBARA
FLIR Systems, Inc.
6769 Hollister Ave,
Goleta, CA 93117
PH: +1 805.690.6600

NEW JERSEY
FLIR Systems, Inc.
65 Challenger Rd
Ridgefield Pk., NJ 07660
PH: +1 201.368.9700

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2020 FLIR Systems, Inc. All rights reserved. 11/2020 rev

20-1419-SEC



The World's Sixth Sense®